

**C 118 - 118W USB C****Features**

12-24V DC Input
 Single Output to 118W Max
 3 Years Warranty



Model	O/P Voltage	O/P Current	Watt
C118 100W PD	5V	3A	15W
	9V	3A	27W
	12V	3A	36W
	15V	3A	45W
	20V	5A	100W
18W USB-C	5V	3A	15W
	9V	2A	18W
	12V	1.5A	18W

Safety Approvals

CE FCC UKCA PSE

Safety Standards

EMI STANDARD EN50498:2010, BS EN 50498: 2010, J55032(H29)
 FCC 47 CFR Part 15 Subpart B, ANSI C63.4-2014

Mechanicals

Case Dimension L91.1 x W37.9 x H28mm

Cable 2000mm ± 30

Case Material UL94-V1

Environmental

Operation Temperature -10 °C – 40 °C
 Storage Temperature -25 °C – 70 °C
 Operation Humidity 5%(0°C) ~ 90%(40°C)
 Storage Humidity 5%~ 95%

Input

Rated Input Voltage 12-24V DC
 Rated Input Current 12A Max input Current

Output

Power 118W Max
 Load Regulation ±5%

Protection

Over Voltage Protection Auto recovery
 Short Circuit Protection Auto recovery
 Over Current Protection Auto recovery