



C 1 2 0 - x x x x y y y y y

xxxx 12-24V  
yyyyy 1mA-8375mA

**Features**

- 12-24V DC Input
- Single Output to 120W Max
- 3 Years Warranty



Model	O/P Voltage	O/P Current	Watt
C120-120001000	12V	10A	120W
C120-190006320	19V	6.32A	120W
C120-240005000	24V	5A	120W

**Input**

Rated Input Voltage	12-24V DC
Rated Input Current	12A Max input Current

**Output**

Power	120W Max
Load Regulation	±5%

**Protection**

Over Voltage Protection	Auto recovery
Short Circuit Protection	Auto recovery
Over Current Protection	Auto recovery

**Safety Approvals**

CE FCC UKCA PSE

**Safety Standards**

EMI STANDARD EN50498:2010, BS EN 50498: 2010, J55032(H29)  
FCC 47 CFR Part 15 Subpart B,ANSI C63.4-2014

**Mechanicals**

Case Dimension L91.1 x W37.9 x H28mm  
Cable UL20276 # 18AWG , 1800mm ± 30  
Case Material UL94-V1

**Environmental**

Operation Temperature	-10 °C – 40 °C
Storage Temperature	-25 °C – 70 °C
Operation Humidity	5%( 0°C) ~ 90%( 40°C)
Storage Humidity	5%~ 95%